

ACCESS CONTROL METHOD AND INFORMATION UTILIZATION APPARATUS

5 The present invention relates to an access control method for controlling the right of accessing and utilizing electronically distributed information and to an apparatus adapted to accessing and utilizing such information.

10 *Q* Currently, various pieces of information are distributed for sale electronically by way of data communication networks including Internet and other satellite communication networks and recording media including CD-ROMs. Such pieces of information typi-
15 cally include the contents of newspapers, magazines, computer programs and recorded videos and audios.

However, there arises the serious problem of pirate copies of these contents that are illegally sold or leased to unauthorized third parties because the
20 electronized contents can be copied without degradation. In particular, there is no effective way of prohibiting the act of making pirate copies if the contents are sold on a payment on delivery basis, in the case where the accounting is done only when the user has obtained
25 the contents. While there may be legal means of confiscating and destructing pirate copies to be taken by the related authorities and that of suing the

pirates for the lost profit to be taken by the infringed, such actions entails enormous time and cost so that a large number of pirate copies are actually on the market.

5 The pay-per-view system is an alternative proposed to bypass the problem of pirate copies. With this system, the contents of information are encoded before delivered to the subscriber so as to prevent the user from utilizing the contents at his or her free will.
10 For example, the user is prohibited from keeping the contents in decoded state and the encoded contents can be decoded each time the user uses them, so that the accounting is done when the encoded contents are decoded. By adopting this method, the accounting can
15 be done without fail because the encoded contents must be decoded when the user uses them.

A typical known pay-per-view system will be described by referring to FIG. 1 of the accompanying drawing.

20 The contents of information to be delivered are encoded by the information provider 1000. The encoded contents 1006 are accompanied by a condition package 1004 including the description on the encoding system, the charge per view, the authorization for printing
25 and/or storage, if any, and other conditions on the use of the contents to complete the information 1002 to be delivered. The information 1002 is then delivered to

00925409
45/150" 47525680

the user terminal 2000 by way of one or more than one communication networks or a CR-ROM and stored in the memory section 2002 before it is retrieved.

When the user requests the user terminal 2000 to
5 operate for displaying, printing or storing the
information, the condition judging section 2004 judges
if the requested operation is authorized or not by
referring to the condition package 1004 of the informa-
tion 1002. If authorized, it issues a command for
10 carrying out the requested operation. Upon receiving
the command, the decoding section 2006 decodes the
encoded content 1006 and the decoded contents are
appropriately displayed on the display screen of a
display unit 2030 by a display processing section 2008,
15 printed to produce a hard copy by a printing unit 2040
under the control of a printing processing section 2010
or stored in an external storage unit 2050 by a storage
processing section 2012. If, on the other hand, the
requested operation is not authorized, the condition
20 judging section 2004 does not issue any command for
carrying out the operation (or issues a command
prohibiting the operation) and the request is refused.

25 *Ans. a27* Since the encoded contents are decoded whenever
they are used so that the user is charged for each
decoding operation of the decoding section 2006.
Specific examples of charging methods that can be used
for the system under consideration include the one for

2025-10-13 15:43:50

5

20

25

to records.

Thus, as described above, known conventional pay-per-view systems are not adapted to have flexibility in setting charges and access requirements for the contents of newspapers and magazines that can change the values in a short period of time because such systems do not take changes in the value of the information they provide and the mode of utilization thereof into consideration.

BRIEF SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide an access control method and an information utilization apparatus that are adapted to have flexibility in setting charges and access requirements for the contents of information that can change the value and the mode of utilization with time.

According to one aspect of the present invention, there is provided an information utilization apparatus comprising: memory means for storing a delivered piece of information including encoded data and applicable time data defining the time period authorizing the use of the encoded data; decoding means for decoding the encoded data stored in the memory means; processing means for carrying out a set of processing steps for an operation requested by the user on the data decoded by the decoding means; and control means for controlling the decoding means and the processing means to operate

at an appropriate time in accordance with the operation requested by the user and the applicable time data stored in the memory means.

In this apparatus, the control means may comprise
5 judging means for determining if the current time
agrees with the time authorizing the use of the encoded
data. In this case, the control means may control the
processing means to operate when the judging means
determines that the current time agrees with the time
10 authorizing the use of the encoded data. The apparatus
may further comprise reserving means for reserving the
operation of the processing means until the time
authorizing the use of the encoded data when the
judging means determines that the current time does not
15 agree with the time authorizing the use of the encoded
data.

According to another aspect of the present
invention, there is provided an information utilization
apparatus comprising: memory means for storing a
20 delivered piece of information including encoded data
and applicable time data defining the time period
authorizing the use of the encoded data; a plurality of
decoding means for decoding the encoded data stored in
the memory means; a plurality of processing means
25 arranged respectively corresponding to the plurality of
decoding means for carrying out one of different sets
of processing steps for an operation requested by the

08032543-0949

user on the data decoded by the decoding means; judging means, upon receiving a request for an operation from the user, for determining if the current time agrees with the time authorizing the use of the encoded data by referring to the applicable time data; and operation command issuing means for issuing a command responding to the request for an operation to the corresponding decoding means and the corresponding processing means if the current time is determined by the judging means to agree with the time authorizing the use of the encoded data by referring to the applicable time data.

According to another aspect of the present invention, there is provided an information utilization apparatus comprising: memory means for storing a delivered piece of information including encoded data and applicable time data defining the time period authorizing the use of the encoded data; decoding means for decoding the encoded data stored in the memory means; plain data storage means for storing the data decoded by the decoding means; a plurality of processing means for carrying out one of different sets of processing steps for an operation requested by the user on the data decoded by the decoding means; judging means, upon receiving a request for an operation from the user, for determining if the current time agrees with the time authorizing the use of the encoded data by referring to the applicable time data; and operation

command issuing means for issuing a command responding to the request for an operation to the decoding means and the corresponding processing means if the current time is determined by the judging means to agree with the time authorizing the use of the encoded data by referring to the applicable time data and the encoded data storage means does not store the encoded data, and issuing a command responding to the request for an operation to the corresponding processing means if the current time is determined by the judging means to agree with the time authorizing the use of the encoded data and the plain data storage means stores the decoded data.

262750" 2152680
15 *Ans. Q37* According to another aspect of the present invention, there is provided an information utilization apparatus comprising: memory means for storing a delivered piece of information including encoded data and applicable time data defining the time period authorizing the use of the encoded data; a plurality of decoding means for decoding the encoded data stored in the memory means; a plurality of processing means arranged respectively corresponding to the plurality of decoding means for carrying out one of different sets of processing steps for an operation requested by the user on the data decoded by the decoding means; judging means, upon receiving a request for an operation from the user, for determining if the current time agrees

with the time authorizing the use of the encoded data
by referring to the applicable time data; operation
command issuing means for issuing a command responding
to the request for an operation to the corresponding
5 decoding means and the corresponding processing means
if the current time is determined by the judging means
to agree with the time authorizing the use of the
encoded data; and operation command reserving means for
reserving the issuance of a command responding to the
10 request for an operation until the time authorizing the
use of the encoded data if the current time is deter-
mined by the judging means not to agree with the time
authorizing the use of the encoded data.

According to another aspect of the present
15 invention, there is provided an information utilization
apparatus comprising: memory means for storing a
delivered piece of information including encoded data
and applicable time data defining the time period
authorizing the use of the encoded data; decoding means
20 for decoding the encoded data stored in the memory
means; plain data storage means for storing the data
decoded by the decoding means; a plurality of process-
ing means for carrying out one of different sets of
processing steps for an operation requested by the user
25 on the data decoded by the decoding means; judging
means, upon receiving a request for an operation from
the user, for determining if the current time agrees

20250113 09:25:00

According to another aspect of the present invention, there is provided an information access control method for use in an information utilization apparatus having a memory for storing a delivered piece
25 of information including encoded data, the method comprising the steps of: picking up the applicable time data added to the encoded data and indicating the time

According to another aspect of the present invention, there is provided an information access control method for use in an information utilization apparatus having a memory for storing a delivered piece of information including encoded data, the method comprising the steps of: picking up the applicable time data added to the encoded data and indicating the time

period authorizing the use of the encoded data in
response to a user request for an operation; and
decoding the encoded data stored in the memory and
carrying out a set of processing steps for the opera-
5 tion requested by the user at an appropriate time
according to the picked up applicable time data.

According to another aspect of the present
invention, there is provided an information access
control method for use in an information utilization
10 apparatus having a memory for storing a delivered piece
of information including encoded data, the method
comprising the steps of: arranging a plurality of
decoding sections for decoding the encoded data stored
in the memory; arranging a plurality of processing
15 sections arranged respectively corresponding to the
plurality of decoding section for carrying out one of
different sets of processing steps for an operation
requested by the user on the data decoded by the
decoding section; judging, upon receiving a request for
20 an operation from the user, for determining if the
current time agrees with the time authorizing the use
of the encoded data by referring to the applicable time
data; and issuing a command responding to the request
for an operation to the corresponding decoding section
25 and the corresponding processing section if the current
time is determined in the judging step to agree with
the time authorizing the use of the encoded data by

referring to the applicable time data.

According to another aspect of the present invention, there is provided an information access control method for use in an information utilization apparatus having a memory for storing a delivered piece of information including encoded data, the method comprising the steps of: arranging a decoding section for decoding the encoded data stored in the memory; arranging a plain data storage section for storing the data decoded by the decoding section; arranging a plurality of processing section for carrying out one of different sets of processing steps for an operation requested by the user on the data decoded by the decoding section; judging, upon receiving a request for an operation from the user, for determining if the current time agrees with the time authorizing the use of the encoded data by referring to the applicable time data; and issuing a command responding to the request for an operation to the decoding section and the corresponding processing section if the current time is determined in the judging step to agree with the time authorizing the use of the encoded data by referring to the applicable time data and the plain data storage section does not store the decoded data, and issuing a command responding to the request for an operation to the corresponding processing section if the current time is determined in the judging step to agree with

202543-0979
"C452580"

the time authorizing the use of the encoded data and the plain data storage section stores the decoded data.

According to another aspect of the present invention, there is provided an information access control method for use in an information utilization apparatus having a memory for storing a delivered piece of information including encoded data, the method comprising the steps of: arranging a plurality of decoding section for decoding the encoded data stored in the memory; arranging a plurality of processing sections arranged respectively corresponding to the plurality of decoding section for carrying out one of different sets of processing steps for an operation requested by the user on the data decoded by the decoding section; judging, upon receiving a request for an operation from the user, for determining if the current time agrees with the time authorizing the use of the encoded data by referring to the applicable time data; issuing a command responding to the request for an operation to the corresponding decoding section and the corresponding processing section if the current time is determined in the judging step to agree with the time authorizing the use of the encoded data; and reserving the issuance of a command responding to the request for an operation until the time authorizing the use of the encoded data if the current time is determined in the judging step not to agree with the time

08932543-09707
462460" 5452580

authorizing the use of the encoded data.

According to another aspect of the present invention, there is provided an information access control method for use in an information utilization apparatus having a memory for storing a delivered piece of information including encoded data, the method comprising the steps of: arranging a decoding section for decoding the encoded data stored in the memory; arranging a plain data storage section for storing the data decoded by the decoding section; a plurality of processing section for carrying out one of different sets of processing steps for an operation requested by the user on the data decoded by the decoding section; judging, upon receiving a request for an operation from the user, for determining if the current time agrees with the time authorizing the use of the encoded data by referring to the applicable time data; issuing a command responding to the request for an operation to the decoding section and the corresponding processing section if the current time is determined in the judging step to agree with the time authorizing the use of the encoded data by referring to the applicable time data and the plain data storage section does not store the decoded data, and issuing a command responding to the request for an operation to the corresponding processing section if the current time is determined in the judging step to agree with the time authorizing the

use of the encoded data and the plain data storage section stores the decoded data; and reserving the issuance of a command responding to the request for an operation until the time authorizing the use of the encoded data if the current time is determined in the judging step not to agree with the time authorizing the use of the encoded data.

20032543 09749
49750" 5452580
10 *enc. a47* Note that the terms "encode/decode" used in this specification includes the meanings of "encrypt/decrypt" and the like. Moreover, note that the term "data" (i.e., encoded or decoded data) includes the meaning of "contents" which appears in the detailed description of the invention.

Additional objects and advantages of the present invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the present invention. The objects and advantages of the present invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out in the appended claims.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the present invention and, together with the general description given above and the detailed description of the

preferred embodiments given below, serve to explain the principles of the present invention in which:

FIG. 1 is a schematic block diagram of a known information distribution system.

5 FIG. 2 is a schematic block diagram of an information distribution system that can be used with a first embodiment of the invention.

10 FIG. 3 schematically illustrates applicable time data including applicable time periods that can be used with any of the first through fourth embodiments of the invention.

15 FIG. 4 schematically illustrates another applicable time data including applicable time periods that can be used with any of the first through fourth embodiments of the invention.

20 FIGS. 5A and 5B schematically illustrate still other sets of time data including applicable time periods and a charge system that can be used with any of the first through fourth embodiments of the invention.

FIG. 6 is a flow chart of a processing operation that can be used for the first embodiment of the invention when there is an occurrence of a request for an action at a user terminal.

25 FIG. 7 is a schematic block diagram of an information distribution system that can be used with the second embodiment of the invention.

08932543 0979
46759 2452589

FIG. 8 is a flow chart of a processing operation that can be used for the second embodiment of the invention when there is an occurrence of a request for display at a user terminal.

5 FIG. 9 is a flow chart of a processing operation that can be used for the second embodiment of the invention when there is an occurrence of a request for an action other than display at a user terminal.

10 FIG. 10 is a flow chart of another processing operation that can be used for the second embodiment of the invention when there is an occurrence of a request for an action other than display at a user terminal.

15 FIG. 11 is a schematic block diagram of an information distribution system that can be used with the third embodiment of the invention.

FIG. 12 is a flow chart of a processing operation that can be used for the third embodiment of the invention when there is an occurrence of a request for display at a user terminal.

20 FIG. 13 is a flow chart of a processing operation that can be used for the third embodiment of the invention when there is an occurrence of a timer event at a user terminal.

25 FIG. 14 is a schematic block diagram of an information distribution system that can be used with the fourth embodiment of the invention.

FIG. 15 is a flow chart of a processing operation

452450" 2152589

that can be used for the fourth embodiment of the invention when there is an occurrence of a request for display at a user terminal.

FIG. 16 is a flow chart of a processing operation that can be used for the fourth embodiment of the invention when there is an occurrence of a request for an action other than display at a user terminal.

FIG. 17 is a flow chart of a processing operation that can be used for the fourth embodiment of the invention when there is an occurrence of a timer event at a user terminal.

FIG. 18 is a flow chart of another processing operation that can be used for the fourth embodiment of the invention when there is an occurrence of a request for an action other than display at a user terminal.

DETAILED DESCRIPTION OF THE INVENTION

Now, the present invention will be described in greater detail by referring to the accompanying drawings that illustrate preferred embodiments of the invention.

<1st Embodiment>

Firstly, the first preferred embodiment will be described by referring to FIGS. 2 through 6 of the accompanying drawing.

FIG. 2 is a schematic block diagram of an information distribution system.

25 The information distributed from the information

08032543 0919
464760" CH52E880

provider 100 to each user terminal 200 includes a condition package 104 and encoded contents 106. The condition package 104 includes a description on the encoding system, a charging system, and applicable time data describing the applicable time period for each mode of utilization of the information. The applicable time includes also "yes" or "no" for the displayability, the printability and the storability of the information respectively as in the case of conventional systems.

Note that the condition package 104 cannot be falsified by the user terminal 200.

It is possible to check to see if the condition package 104 has been falsified by adding an electronic signature or the like thereto. If a falsification is detected in this check, the access processing after the detection of the falsification is stopped, thereby preventing the unauthorized access by way of the falsification of the condition package 104.

The falsification check by the electronic signature is realized by the following method, for example. First, the condition package 104 is added with the information which is the condition package encrypted with a secret key. Second, in the user terminal 200, the added information is decrypted with a public key and the decrypted information is compared with the condition package 104. Finally, an occurrence of the falsification is known if a result of the

expression of the table of FIG. 3. Symbols of ○ and × are used to indicate if each of the modes of utilization is authorized or not for use for the period specified there.

5 Various different formats may be conceivable to express the applicable time data.

Referring to FIG. 5A, a charge system may be added to the applicable time data of FIG. 4. Alternatively, the charge system may be so arranged as to correspond to the modes of utilization of information as shown in FIG. 5B. With such an arrangement, there may be provided a highly comprehensive charge system.

10

Thus, with this first embodiment, the applicable time data as illustrated in FIG. 3, FIG. 4, FIG. 5A, FIG. 5B or in some other format are contained in the condition package 104 of the information 102.

15

Ans. ab Thus, data such as "yes" or "no" for the displayability, the printability and the storability of the information may be omitted if such applicable time data is used.

20

Upon receiving a request from the user for displaying, printing and/or storing the information 102, the condition judging section 204 of the user terminal 200 judges if the request can be met or not by comparing for each requested mode of utilization the clock information read from the clock 206 (including the current time and the date in this embodiment) and the

25

applicable time period for that mode of utilization
specified in the applicable time data in the condition
package 104 to determine if the contents of the
information 102 are available for the requested mode of
5 utilization.

If the condition judging section 204 determines
that the contents of the information are available for
the requested mode of utilization, it issues a command
for action to the decoding section 208, 212 or 216,
10 whichever appropriate, whereas it does not issue any
command if it determines that the contents are not
available. The decoding section 208, 212 or 216,
whichever appropriate, carries out a predetermined
processing operation only for the command for action it
15 receives from the condition judging section 204.

Note that the plain contents obtained from the
decoding section are not accessible from other than the
processing section uniquely connected to that decoding
section.

20 *See a¹* Each of the condition judging section 204, the
clock 206, the decoding section 208, the display
processing section 210, the decoding section 212, the
printing processing section 214, the decoding section
216 and the storage processing section 210 in FIG. 2
25 may be realized either by means of software or by means
of hardware. Note that each of these components are so
configured that the user cannot modify any part thereof.

0052543-00297
462760-452680

Additionally, these components may be realized in the form a hermetically sealed unitary chip that cannot be damaged from outside.

If the clock 206 is provided as a piece of hardware, it may be realized in the form of an unreplaceable device that is initialized by the information provider 100.

Now, the operation of the embodiment will be described.

FIG. 6 is a flow chart of a processing operation when there is an occurrence of a request for an action at a user terminal.

When a request for an action that may be an action for displaying, printing or storing a specific piece of information provided by the information provider 100 is entered to a user terminal 200 by the user, the condition judging section 204 picks up the condition package 104 of the information 102 (step S11). Note that the condition package 104 contains "yes" or "no" for each mode of utilization so that the request is turned down at this step if the requested mode of utilization is not authorized at all.

The condition judging section 204 also reads the current time and date from clock 206 (step S12).

Ans. a3 Note that step S12 may precedes step S11 or steps S11 and 12 may be carried out concurrently.

Then, the condition judging section 204 judges if

the requested action can be taken or not by comparing for each requested mode of utilization the current time and date read from the clock 206 and the applicable time period for that mode of utilization specified in the applicable time data in the condition package 104 to determine if the contents of the information 102 are available for the requested mode of utilization (step S13).

10 *Ans. 29* If it is determined in step S14 that the requested action (for display, printing or storage) can be taken, it issues a command for the action to the related decoding section (step S15). Note that, in this embodiment, a command is issued to the decoding section 208 for a displaying action, to the decoding section 15 212 for a printing action and/or to the decoding section 214 for a storing action.

Then, upon receiving a command, the decoding section decodes the encoded contents 106 and the related processing section outputs them to the related unit (step S16). More specifically, the plain contents are displayed on the display unit 230 by the display processing section 208, printed by the printing unit 240 under the control of the printing processing section 214 and/or stored in the external storage unit 20 250 by the external storage processing section 216.

If, on the other hand, it is determined in step S14 that the requested action is prohibited, the

003543-0979
00260-04522680

08924543-09127

08924543-09127

08924543-09127

0894543-091707

08924543-09127

08924543-09127

and only the relevant one or more than one of the display processing section 208, the printing processing section 214 and the storage processing section 216 operate for the specified action in response to the command issued from the condition judging section 204.

While a decoding section is provided for each of the modes of utilization in the above embodiment, a single decoding section may be shared by all the modes of utilization. With such an arrangement, again, the condition judging section 204 issues a command for an action to the display processing section 208, the printing processing section 214 and the storage processing section 216 simultaneously and only the relevant one or more than one of the display processing section 208, the printing processing section 214 and the storage processing section 216 operate for the specified action in response to the command issued from the condition judging section 204.

<2nd Embodiment>

While the first embodiment is designed to decode the encoded contents each time they are utilized, the time required for printing and/or storage can be reduced when the contents decoded for display are used also for printing and/or storage and the operation of displaying the contents takes place prior to printing and/or storage.

The second embodiment is exactly designed to

reduce the time required for printing and/or storage when the contents decoded for display are used also for printing and/or storage and the operation of displaying the contents takes place prior to printing and/or storage.

FIG. 7 is a schematic block diagram of an information distribution system.

10 *Ans. a17* As in the case of the first embodiment, the information distributed from the information provider 100 to each user terminal 300 includes a condition package 104 and encoded contents 106. The condition package 104 includes a description on the encoding system, a charging system, and applicable time data describing the applicable time period for each mode of utilization of the information. The applicable time data includes also "yes" or "no" for the displayability, the printability and the storability of the information respectively as in the case of conventional systems.

20 Note that the condition package 104 cannot be falsified by the user terminal 300.

25 It is possible to check to see if the condition package 104 has been falsified by adding an electronic signature or the like thereto. If a falsification is detected in this check, the access processing after the detection of the falsification is stopped, thereby preventing the unauthorized access by way of the falsification of the condition package 104.

03932543 09 27 15 00 54 52 53 0

08932543-09797
202760-2452E80

The falsification check by the electronic signature is realized by the following method, for example. First, the condition package 104 is added with the information which is the condition package encrypted with a secret key. Second, in the user terminal 300, the added information is decrypted with a public key and the decrypted information is compared with the condition package 104. Finally, an occurrence of the falsification is known if a result of the comparison does not indicate a coincidence.

The information 102 is delivered to the user terminal 300 by the information provider 100 by way of one or more than one communication networks including Internet and/or other satellite communication networks or a storage medium such as a CD-ROM.

The information is provided with an identifier for the ease of control.

The applicable time data as described above by referring to the first embodiment are also used for this embodiment. More specifically, with this first embodiment, the applicable time data as illustrated in FIG. 3, FIG. 4, FIG. 5A, FIG. 5B or in some other format are contained in the condition package 104 of the information 102.

25 *enaa's* Thus, data such as "yes" or "no" for the displayability, the printability and the storability of the information may be omitted if such the applicable time

~~data is used,~~

Upon receiving a request from the user for displaying, printing and/or storing the information 102, (provided that the contents of the information are already displayed when an operation other than display is requested,) the condition judging section 304 of the user terminal 300 judges if the request can be met or not by comparing for each requested mode of utilization the clock information read from the clock 306 (including the current time and the date in this embodiment) and the applicable time period for that mode of utilization specified in the applicable time data in the condition package 104 to determine if the contents of the information 102 are available for the requested mode of utilization.

If the condition judging section 304 determines that the contents of the information are available for any of the requested modes of utilization, it issues a command for action to the decoding section 308 and the relevant one or more than one of the display processing section 312, the printing processing section 314 and the storage processing section 316, whereas it does not issue any command if it determines that the contents are not available. The decoding section 308 and the relevant one or ones of the display processing section 312, the printing processing section 314 and the storage processing section 316 carry out

08932543-00497

a predetermined processing operation only for the command for action they receive from the condition judging section 304.

5 Note that the plain contents obtained from the decoding section 308 are stored in the plain contents storage section 310 but are not accessible from other than the display processing section 312, the printing processing section 314 and the storage processing section 316.

10 *emb 13* Each of the condition judging section 304, the clock 306, the decoding section 308, the plain contents storage section 310, the display processing section 312, the printing processing section 314 and the storage processing section 316 described above may be realized
15 either by means of software or by means of hardware. Note that each of these components are so configured that the user cannot modify any part thereof. Additionally, these components may be realized in the form a hermetically sealed unitary chip that cannot be
20 damaged from outside.

If the clock 306 is provided as a piece of hardware, it may be realized in the form of an unreplaceable device that is initialized by the information provider 100.

25 Now, the operation of this second embodiment will be described.

FIG. 8 is a flow chart of a processing operation

00932543-0979
20250922

S24 that the requested action is prohibited, the condition judging section 304 does not issue any command and the request is turned down.

Alternatively, if it is determined in step S24
5 that the requested action is prohibited, it may be so arranged that the condition judging section 304 issues a command prohibiting the requested action and a message saying "the requested action is prohibited at the requested time", to which the time period that
10 allows the requested action to be taken may be added or not, is displayed to notify the user thereof.

FIG. 9 is a flow chart of a processing operation when there is an occurrence of a request for an action other than display at a user terminal.

15 When a request for an action other than display that may be a request for printing or storage is entered to a user terminal 300 by the user, the processing operation is terminated if it is found in step S31 that the operation for display has not been
20 carried out yet and hence the plain contents to be utilized are not stored in the plain contents storage section 310. It may be so arranged that a message "no display" or "display first" is displayed to notify the user of the current situation.

25 *also* If, on the other hand, it is found in step S31 that the operation for display has been carried out and hence the plain contents to be utilized are stored in

08032543-004707

the plain contents storage section 310, the condition
judging section 304 picks up the condition package 104
of the information 102 of the information 102 to be
utilized (step S32). If the condition package 104
5 contains "no" for the requested mode of utilization,
the request is turned down at this time.

The condition judging section 304 also reads the
current time and date from clock 306 (step S33).

ans. a16 Note that step S33 may precedes step S32 or steps
10 S32 and 33 may be carried out concurrently.

Then, the condition judging section 304 judges if
the requested operation can be authorized at the
current time by comparing the current time and date and
the applicable time period for the requested mode of
15 utilization specified in the applicable time data in
the condition package 104 to determine if the contents
of the information 102 are available for the requested
mode of utilization (step S34).

If it is determined in step S35 that the requested
20 operation can be made, it issues a command for the
operation to the printing processing section 314 or the
storage processing section 316, whichever appropriate
(step S36).

ans. a17 Then, upon receiving a command, the processing
25 section outputs the plain contents to the related unit
330 for display (step S37). Thus, the plain contents
may be printed by the printing unit 240 under the

0892543-097
26250-097

control of the printing processing section 314 or
stored in the external storage unit 230 by the storage
processing section 316.

5 If, on the other hand, it is determined in step
S35 that the requested action is prohibited, the
condition judging section 304 does not issue any
command and the request is turned down.

10 Alternatively, if it is determined in step S34
that the requested action is prohibited, it may be so
arranged that the condition judging section 304 issues
a command prohibiting the requested action and a
message saying "the requested action is prohibited at
the requested time", to which the time period that
allows the requested action to be taken may be added or
15 not, is displayed to notify the user thereof.

FIG. 10 is a flow chart of an alternative
processing operation when there is an occurrence of a
request for an action other than display at a user
terminal.

20 Only the difference between FIG. 9 and FIG. 10
will be described here.

According to FIG. 9, the processing operation is
terminated if it is found in step S31 that the opera-
tion for display has not been carried out yet and hence
25 the plain contents to be utilized are not stored in the
plain contents storage section 310.

also. a 18 According to FIG. 10, on the other hand, the

08932543 09197
152150 0452680

routines as described earlier by referring to FIG. 8
are carried out in steps S42 and 43 if it is found in
step S41 that the operation for display has not been
carried out yet and hence the plain contents to be
5 utilized are not stored in the plain contents storage
section 310 so that, if the plain contents can be
displayed, the encoded contents are decoded and
displayed automatically.

More specifically, in step S42, the condition
10 judging section 304 picks up the condition package 104
of the target information 102 and also the current time
and date from the clock 306 and judges if the requested
operation can be authorized at the current time by
comparing the current time and date and the applicable
15 time period for the requested mode of utilization
specified in the applicable time data in the condition
package 104 to determine if the contents of the
information 102 are available for the requested mode of
utilization.

20 If it is determined in step S42 that the requested
display operation can be made, it issues a command for
the operation to the decoding section 308 and the
display processing section 314 (step S43). As a result,
the decoded contents are stored in the plain contents
25 storage section 310 and displayed on the display unit
330. After step S43, the operation follows steps S44
through S49, which are identical with steps S32 through

08032543 0979
452150 24522680

S37 described above.

If, on the other hand, it is determined in step S42 that the requested operation is prohibited, the condition judging section 304 does not issue any command and the request is turned down. Alternatively, the condition judging section 304 may issue a command for prohibiting the requested operation and a message saying "the requested display is prohibited at the requested time", to which the time period that allows the requested action to be taken may be added or not, is displayed to notify the user thereof.

While a display operation is carried out prior to any other mode of utilization in the above description of the second embodiment, step S31 may be omitted from FIG. 9 or steps S41 through S43 may be omitted from FIG. 10 if a display operation is not discriminated from the other modes of utilization. Then, the condition judging section 304 issues a command for an operation to the related processing section if there are no plain contents.

Any known technique may be used for charging fees for the purpose of the present invention.

Thus, the above described embodiment can flexibly set requirements to be met by the user for utilizing the contents of a piece of information that can change the value and the mode of utilization with time as a function of the time and date of utilization.

20 The system configuration of FIG. 11 differs from
that of FIG. 2 in that a command memory 220 is provided
in the third embodiment to store the commands for an
action that is not authorized at the current time and
date but can be authorized at some other time and date
25 in the future, that a command from the condition
judging section 204 is sent to a relevant one of the
decoding sections and the corresponding processing

section and that the clock information from the clock 206 are sent also to the command memory section 220.

5 The command memory section 220 operates for storing the commands for actions sent from the condition judging section 204 and hold them for the future. The command memory section 220 is provided with timers that correspond to the respective decoding sections 208, 212 and 216. Each of these timers is used to specify the time and date when the requested action is authorized so that it generates a timer event when a predetermined time period has elapsed. Once a timer event is generated, the command memory section 220 transmits the related command it stores for an action to the related decoding section (and the related processing section).

10

15

also 219 Each of the condition judging section 204, the clock 206, the decoding section 208, the display processing section 210, the decoding section 212, the printing processing section 214, the decoding section 216, the storage processing section 210 and the command memory section 220 described above may be realized either by means of software or by means of hardware. Note that each of these components are so configured that the user cannot modify any part thereof. Additionally, these components may be realized in the form of a hermetically sealed unitary chip that cannot be damaged from outside.

20

25

If the clock 206 is provided as a piece of hardware, it may be realized in the form of an unreplaceable device that is initialized by the information provider 100 so that any other clock may not be used there.

Now, the operation of this third embodiment will be described by referring to the flow charts of FIGS. 12 and 13.

In FIG. 12, steps S51 through S56 are identical with steps S11 through S16 of FIG. 6. In other words, if the requested action is authorized to be taken at the current time and date, it is carried out at steps S51 through S56.

Under this condition, the command memory section 220 sends a command for the action only to the related components and not to any other ones.

In step S54, if it is determined that the requested action is prohibited at the time and date of the request but there exists a time period during which the request can be authorized, the condition judging section 204 sends a control signal representing a command for the action that has to be reserved and data on the time and date when the request is authorized and hence the action can be taken to the command memory section 220. Note that the control signal representing a command for the action that has to be reserved may be replaced by the presence or absence of data on the time

5

10

15

20

25

0832543 "094"
45749

If the user cannot make an appointment for printing or storing the article at that time, it is very cumbersome and painstaking for him or her to read the article once again after a predetermined period of time to issue a request for printing or storage. He or she may have totally forgotten the article by that time. This embodiment can accommodate such situations to relieve the subscriber from the cumbersome and painstaking effort of memorizing the time and date when the request for printing and/or storing the article is authorized.

Since the appointment for storing the article can be automatically stored in the memory of the embodiment, the subscriber does not have to read the article for another time when he or she issues a request for storing it. Thus, the subscriber can enjoy preparing "a scrap book" by picking up only those contents he or she wants out of the contents provided by a pay-per-view system.

<4th Embodiment>

Now, the fourth embodiment of the invention will be described.

A request for an action is turned down in the second embodiment if the requested action is not authorized at the current time and date.

This embodiment differs from the second one in that, if the requested action is not authorized at the current time and date, it stores the request if the

requested action can be authorized sometime in the future so that the requested action is carried out automatically when the time comes where the request is authorized.

5 FIG. 14 is a schematic block diagram of an information distribution system.

 The following description will be focused on the difference between the two embodiments and the components that are similar to or same as those of the
10 second embodiment will not be described any further.

 The system configuration of FIG. 14 differs from that of FIG. 7 in that a command memory 320 is provided in the fourth embodiment to store the commands for an action that is not authorized at the current time and
15 date but can be authorized at some other time and date in the future, that a command from the condition judging section 304 is sent to a relevant one of the decoding sections (and the corresponding processing section) and that the clock information from the clock
20 306 are sent also to the command memory section 320.

sem. a207 The command memory section 320 operates for storing the commands for actions sent from the condition judging section 304 and hold them for the future. The command memory section 320 is provided with a timer.
25 The timer is used to specify the time and date when the decoding section 308 is authorized to decode the encoded contents for the requested action so that it

generates an timer event when a predetermined time period has elapsed. Once a timer event is generated, the command memory section 320 transmits the related command it stores for an action to the decoding section 308 (and the related processing section).

Each of the condition judging section 304, the clock 306, the decoding section 308, the plain contents storage section 310, the display processing section 312, the printing processing section 314, the storage processing section 316 and the command memory section 320 described above may be realized either by means of software or by means of hardware. Note that each of these components are so configured that the user cannot modify any part thereof. Additionally, these components may be realized in the form a hermetically sealed unitary chip that cannot be damaged from outside.

If the clock 306 is provided as a piece of hardware, it may be realized in the form of an unreplaceable device that is initialized by the information provider 100 so that any other clock may not be used there.

Now, the operation of this fourth embodiment will be described by referring to the flow charts of FIGS. 15 through 17.

FIG. 15 is a flow chart of a processing operation when there is an occurrence of a request for display at a user terminal. FIG. 16 is a flow chart of

a processing operation when there is an occurrence of a request for an action other than display at a user terminal. FIG. 17 is a flow chart of a processing operation when there is an occurrence of a timer event at a user terminal.

Firstly, the operation of processing a request for display of this embodiment will be described by referring to the flow charts of FIG. 15.

In FIG. 15, steps S71 through S76 are identical with steps S21 through S26 of FIG. 8. In other words, if the requested action is authorized to be taken at the current time and date, it is carried out at steps S71 through S76.

Under this condition, the command memory section 320 sends a command for the action only to the related components and not to any other ones.

In step S74, if it is determined that the requested action is prohibited at the time and date of the request but there exists a time period during which the request can be authorized, the condition judging section 304 sends a control signal representing a command for the action that has to be reserved and data on the time and date when the request is authorized and hence the action can be taken to the command memory section 320. Note that the control signal representing a command for the action that has to be reserved may be replaced by the presence or absence of data on the time

and date when the request for the action is authorized. The command memory section 320 stores the command for the action in the future and sets the timer for the time and date when the request for the action is
5 authorized (step S77). It may be so arranged that a message saying that the request is reserved is displayed to notify the user thereof under this condition.

When the timer event occurs after the predetermined time period and the requested action is a display
10 operation (step S91) in FIG. 17, the command memory section 320 sends the command for the action it stores to the decoding section 308 and the display processing section 312 (step S92). Upon receiving the command for the action, the decoding section 308 decodes the
15 encoded contents to be utilized and the display related processing section transmits a corresponding output to the unit connected to it (step S93).

Next, the operation of processing a request for other than display of this fourth embodiment will be
20 described by referring to the flow charts of FIG. 16.

In FIG. 16, steps S81 through S86 are identical with steps S31 through S36 of FIG. 9. In other words, if the requested action is authorized to be taken at the current time and date, it is carried out at steps
25 S81 through S86.

Under this condition, the command memory section 320 of FIG. 14 sends a command for the action only to

the related components and not to any other ones.

On the other hand, if it is determined in step S81 that the requested action is prohibited at the time and date of the request but there exists a time period during which the request can be authorized, the condition judging section 304 sends a control signal representing a command for the action that has to be reserved and data on the time and date when the request is authorized and hence the action can be taken to the command memory section 320 and sets the timer (step S88). As in the case of the third embodiment, it may be so arranged that a message saying that the request is reserved is displayed to notify the user thereof under this condition.

Referring further to FIG. 17, when the timer event occurs after the predetermined time period and if it is found (step S91) that the request is for other than display, the command memory section 320 sends the command for the action it stores to the related processing section, which may be the printing processing section 314 or the storage processing section 316 (step S94). Upon receiving the command for the action, the related processing section transmits a corresponding output to the unit connected to it on the basis of the plain contents decoded and stored in the plain contents storage section 310 (step S95).

lemau If the command memory section 320 stores more than

one commands, it carries out the processing operation of FIG. 17 for each and all of the stored commands. It may be so arranged that a command for display is issued first if same contents are reserved for both display and another mode of utilization other at a same appointed time or two respective appointed times that are close to each other.

FIG. 18 is a flow chart of another processing operation when there is an occurrence of a request for an action other than display at a user terminal.

In FIG. 18, steps S101 through S109 are identical with steps S41 through S49 of FIG. 10. In other words, if the requested action is authorized to be taken at the current time and date, it is carried out at steps S101 through S109. On the other hand, the routines as described earlier by referring to FIG. 8 are carried out in steps S42 and 43 if it is found in step S41 that the operation for display has not been carried out yet and hence the plain contents to be utilized are not stored in the plain contents storage section 310 so that, if the plain contents can be displayed, the encoded contents are decoded and displayed automatically.

Under this condition, the command memory section 320 of FIG. 14 sends a command for the action only to the related components and not to any other ones.

On the other hand, if it is determined in step

2025 RELEASE UNDER E.O. 14176

5 S101 that there exists the requested plain contents,
the condition judging section 304 sends a control
signal representing a command for the action that has
to be reserved and data on the time and date when the
request is authorized and hence the action can be taken
to the command memory section 320 and sets the timer
(step S110) even though the requested action is
prohibited at the time and date of the request but
there exists a time period during which the request can
10 be authorized. As described above, it may be so
arranged that a message saying that the request is
reserved is displayed to notify the user thereof under
this condition.

15 If it is determined in step S101 that there do not
exist any plain contents and the requested display
operation is not authorized, the condition judging
section 304 makes an appointment in the command memory
section 320 for the requested action other than display
and also for the requested display operation, if such a
20 request exists (step S111).

elim. A24 When the timer event occurs after the predeter-
mined time period, the processing steps are taken in a
manner as described above by referring to FIG. 17. If
the command memory section 320 stores more than one
25 commands as described above, it carries out the
processing operation of FIG. 17 for each and all of the
stored commands. It may be so arranged that a command

above described embodiments is controlled on the basis of the data on applicable time and date stored in condition package 104 and the current time and date available from the clock 206 (306), only data on dates
5 may be used for controlling the operation.

For the purpose of the invention, the user terminal may be used as a server apparatus.

For example, the user terminal of any of the first through fourth embodiments may be connected to a user
10 computer typically by way of LAN so that a request for display may be issued from the user computer to the user terminal by specifying the identifier of a piece of information. Upon receiving the request, the user terminal follows a set of processing steps as described
15 above and transfers the display data to the user computer instead of sending them to the display unit of the terminal if the request is authorized (or when the time event for the reserved display operation occurs). The requesting user computer then outputs the received
20 display data to the display unit. Of course, the display data cannot be decoded into plain contents. The above description may be applied to a request for printing as well.

25 *ems. 25* It may alternatively be so arranged that, upon receiving a request for storage, the user terminal follows a set of processing steps as described above and transfer the plain contents corresponding to the

request to the user computer instead of sending them to the storage unit of the terminal if the request is authorized any time thereafter (or a time comes when the request is authorized any time thereafter). The requesting user computer then stores the plain contents it receives. Since the use of the plain contents is authorized anytime thereafter, the user computer can utilize the plain contents it stores in any fashion.

Many other modifications of the above embodiments may be conceivable.

Ans. (2267) Alternatively, the user terminal may be used only as a server of the user terminal of any of the first through fourth embodiments may be provided with the functional feature of a server.

While the present invention is described in terms of access right that can change with time. The fee to be charged for utilizing the contents of a piece of information may be changed with time according to the invention. If such is the case, a table showing the charge for any given time and date (or date) of utilization as illustrated in one of FIGS. 3 through 5B may be stored in advance so that the charge for a specified mode of utilization may be automatically calculated for a given time and date by a built-in charge processing section by referring to the table and the current time and date of the clock. Thus, an article of a newspaper or a magazine may be charged

[illegible][illegible][illegible][illegible]

According to the invention, the time for an access to the provided information may be appointed in advance so that the access may be realized without requiring any further command to be issued from the user.

5 Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the present invention in its broader aspects is not limited to the specific details, representative devices, and illustrated examples shown and described herein.

10 Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

442150-452533